



# Machinery Parts USA CORP.



231/530KYMBW37W906AC4 Bearing 2D drawings and 3D CAD models

20.866 Inch | 530 Millimeter x 34.252 Inch | 870 Millimeter x 10.709 Inch | 272 Millimeter  
**TIMKEN 231/530KYMBW37W906AC4 Spherical Roller Bearings**

Bearing No. 231/530KYMBW37W906AC4

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	629.7
EAN	0087796197879
Product Group	M06288
Internal Clearance	C4-Extra Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Adapter Part Number - Millimeter	H31/530 (Specify bore)
Withdrawal Sleeve	AH31/530 AOH31/530 (Specify bore)
Inch - Metric	Metric
Long Description	530MM Tapered Bore; 870MM Outside Diameter; 272MM Width; C4-Extra Loose Clearance; Adapter Mount; Double Row of Spherical Roller Bearings;



## Machinery Parts USA CORP.

	Bronze Cage Material; Open Enclosure; Relubricatable; Adapter
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	8482.30.80.00
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	231/530 KYMBW37W906AC4
Weight / LBS	1,387
d	20.866 Inch   530 Millimeter
D	34.252 Inch   870 Millimeter
B	10.709 Inch   272 Millimeter
Design Unit	METRIC
Bore Taper	1/12
Bearing Weight	650.600 Kg
Cage Type	YMB
UPC Code	087796197879
d - Bore	530.000 mm
D - Outer Diameter	870.000 mm
B - Inner Ring Width	272 mm
B - Outer Ring Width	272.000 mm
R - Inner Ring To Clear Radius <sup>1</sup>	6.000 mm
r - Outer Ring To Clear Radius <sup>2</sup>	6.000 mm
da - Inner Ring Backing Diameter	603.000 mm
Da - Outer Ring Backing	793.000 mm



## Machinery Parts USA CORP.

Diameter	
C0 - Static Radial Rating	15100000 N
C1(2) - Dynamic Radial Rating (Two-Rows)	8530000 N
e - ISO Factor <sup>3</sup>	0.3
Y0 - ISO Factor <sup>4</sup>	2.27
Y1 - ISO Factor <sup>5</sup>	3.38
Y2 - ISO Factor <sup>6</sup>	2.22
Reference Thermal Speed Rating (Grease)	310
Reference Thermal Speed Rating (Oil) <sup>7</sup>	340
Cg - Geometry Factor <sup>8</sup>	0.1109